



PO Box 5992, Sharjah,
United Arab Emirates
Tel: +971 6 534 4310
Fax: +971 6 5344 210
Email: spcsalesme@esisys.com
www.esisys.com

DISPENSING

SINGLE POLY RACK™ SYSTEM

Economical, space-saving solution to storing and dispensing from 55-gallon drums.

The system consists of separate single Poly-Packer, single Poly Stacker, Universal Well Liner and Poly Shelf.

The Poly Stacker allows for stacking of second 55-gallon drum.

The system holds 1,600 lbs and the Poly Racker features a 66-gallon sump capacity!



UNIVERSAL™ WELL LINER

The Universal Well Liner provides extra spill protection.



MULTI-PURPOSE RACKER/STACKER™

Maximize floor space with the Multi-Purpose Racker/Stacker.

One Multi-Purpose Racker/Stacker holds up to two 55-gallon drums.

The stackable unit allows you to store up to four 55-gallon drums. The

unit can be placed on the floor (no sump) or on the Poly-Slim

Line 6000 pallet (Product No. 5400-YE see page 23). Use with the Poly-Shelf (Product No. 6003-YE see page 16) for easy dispensing into 5- or 6-gallon pails. Forkliftable!

*EPA compliant when used In conjunction with product # 5400.

LOADING IS EASY!



1. Secure drum with proper cinch strap and lift drum with forklift.

2. Guide drum and orient onto the Poly-Racker.

3. Once drum is placed securely on the PolyRacker, remove cinch strap and back away.

SPECIFICATIONS

	MULTI-PURPOSE RACKER/STACKER™	UNIVERSAL® WELL LINER
Product No.	6004-YE	6005-BK
Dimensions	48.5" l x 41" w x 20" h 123 cm x 104 cm x 51 cm	12.75" l x 15.5" w x 2.5" h 32 cm x 39 cm x 6 cm
Weight	87 lbs / 39.15 kg	1lb / 0.45 kg
Load Bearing Capacity UDL	2400 lbs / 1080 kg	
Sump Capacity		0.5 gal / 1.9 litres
Regulations	EPA 40 CFR 264.175	

SPECIFICATIONS

	SINGLE POLY RACKER™	SINGLE POLY STACKER™
Product No.	6006-YE	6007-YE
Dimensions	31" l x 53" w x 32" h 79 cm x 134 cm x 81 cm	31" l x 40.5" w x 20" h 79 cm x 103 cm x 51 cm
Weight	95 lbs / 42.75 kg	50 lbs/ 22.5 kg
Load Bearing Capacity UDL	1600 lbs / 720 kg	800 lbs / 360 kg
Sump Capacity	66 gal / 250.8 litres	
Regulations	EPA 40 CFR 264.175	