



PO Box 5992, Sharjah,
United Arab Emirates
Tel: +971 6 534 4310
Fax: +971 6 5344 210
Email: spcsalesme@esisys.com
www.esisys.com

DISPENSING

POLLY-RACKER™

The centerpiece of the Poly-Rack System is the Poly-Packer, a unique, one-piece polyethylene rack that holds two 55gallon drums securely in place. A massive 100-plus gallon containment sump ensures spill safety even in worst-case drum leaks. And the deep dispensing well easily holds 5gallon pails while containing incidental spills and splashes in a ribbed bottom — without contaminating the sump.

Dispensing wells have a scalloped edge so pails can be easily removed. Two (2) drain plugs standard. Poly-Racker can be transported by forklift as separate pieces.

POLY-STACKER™

Combine a single Poly-Stacker with Poly-Backer to stack up to four drums. Add another Poly-Stacker and you have a storage system that holds six drums and is rated to hold 3,000 lbs UDL.

Each Poly-Stacker holds two 55-gallon drums and can quickly be stacked with a forklift. Any spills from the second and third levels fall into the dispensing well for containment and easy clean-up. Combined, Poly-Backer and Poly-Stacker make up the most efficient drum storage and dispensing system you can buy.

POLY-SHELF

Save money—prevent spills! Increase safety and productivity when you add the Poly-Shelf to your PolyBack System. It easily attaches to a Poly-Stacker and allows simultaneous dispensing from all drums. Spills? A hole in the bottom of the Poly-Shelf drains into the dispensing well in the Poly-Backer.



- ☐ Forkliftable as separate pieces
- ☐ Scalloped well for easy pail removal



- ❑ Dual drain plugs
- ❑ Deep dispensing well holds 5-gallon pails

SPECIFICATIONS			
	POLY-RACKER™	POLY-STACKER™	POLY-SHELF™
Product No.	6000-YE	6002-YE	6003-YE
Dimensions	49" l x 52.5" w x 22.5" h 124 cm x 133 cm x 57 cm	49" l x 41" w x 13" h 124 cm x 104 cm x 33 cm	17" l x 22" w x 17.5" h 43 cm x 56 cm x 44 cm
Weight	120 lbs / 54kg	56 lbs / 25.2 kg	10 lbs / 4.5kg
Load Bearing Capacity UDL	3000 lbs / 1350kg	2400 lbs / 1080 kg	60 lbs / 27kg
Sump Capacity	102 gal / 387.6 litres		
Regulations	EPA 40 CFR 264.175		