



PO Box 5992, Sharjah,
United Arab Emirates
Tel: +971 6 534 4310
Fax: +971 6 5344 210
Email: spcsalesme@esisys.com
www.esisys.com

DISPENSING

SINGLE POLY RACK™ SYSTEM



Economical, space-saving solution to storing and dispensing from 55-gallon drums.

The system consists of separate single Poly-Packer, single Poly Stacker, Universal Well Liner and Poly Shelf.

The Poly Stacker allows for stacking of second 55-gallon drum.

The system holds 1,600 lbs and the Poly Racker features a 66-gallon sump capacity



UNIVERSAL™ WELL LINER

The Universal Well Liner provides extra spill protection.



MULTI-PURPOSE RACKER/STACKER™

Maximize floor space with the Multi-Purpose Racker/Stacker. One Multi-Purpose Racker/Stacker holds up to two 55-gallon drums. The stackable unit allows you to store up to four 55-gallon drums. The unit can be placed on the floor (no sump) or on the Poly-Slim Line 6000 pallet (Product No. 5400-YE see page 23). Use with the Poly-Shelf (Product No. 6003-YE see page 16) for easy dispensing into 5 or 6 gallon pails. Forkliftable!

*EPA compliant when used In conjunction with product # 5400.

LOADING IS EASY!



1. Secure drum with proper cinch strap and lift drum with forklift.

2. Guide drum and orient onto the Poly-Racker.

3. Once drum is placed securely on the PolyRacker, remove cinch strap and back away.

SPECIFICATIONS

| | MULTI-PURPOSE RACKER/STACKER™ | UNIVERSAL® WELL LINER |
|---------------------------|--|---|
| Product No. | 6004-YE | 6005-BK |
| Dimensions | 48.5" l x 41" w x 20" h 123 cm x 104 cm x 51 cm | 12.75" l x 15.5" w x 2.5" h 32 cm x 39 cm x 6 cm |
| Weight | 87 lbs / 39.15 kg | 1lb / 0.45 kg |
| Load Bearing Capacity UDL | 2400 lbs / 1080 kg | |
| Sump Capacity | | 0.5 gal / 1.9 litres |
| Regulations | EPA 40 CFR 264.175 | |

SPECIFICATIONS

| | SINGLE POLY RACKER™ | SINGLE POLY STACKER™ |
|---------------------------|---|---|
| Product No. | 6006-YE | 6007-YE |
| Dimensions | 31" l x 53" w x 32" h 79 cm x 134 cm x 81 cm | 31" l x 40.5" w x 20" h 79 cm x 103 cm x 51 cm |
| Weight | 95 lbs / 42.75 kg | 50 lbs/ 22.5 kg |
| Load Bearing Capacity UDL | 1600 lbs / 720 kg | 800 lbs/ 360 kg |
| Sump Capacity | 66 gal / 250.8 litres | |
| Regulations | EPA 40 CFR 264.175 | |